CIL

Compact Integrated Laser



Main Advantages & Features

- Based on cutting-edge modern diode-pumped technology
- High repetition rate (up to 10pps continuously)
- Eyesafe rangefinding
- Compact, lightweight, single LRU
- Designed and tested IAW-MIL-STD

Applications

- Integrated part of air defense weapon systems
- Stand-alone unit for gunfire control systems
- Integrated sight for EO payloads/clusters

Elbit Systems™
ISTAR & EW

CIL

Compact Integrated Laser

Technical Data

Transmitter type	Diode-pumped,
Erbium glass	
	1.54 µm (eyesafe)
Output energy, min	10 mJ
(after 3 sec.)	
Repetition rate	10 pps
Beam divergence	1.5 mRad,
adjustable	
Range	
- Minimum	100 m
- Maximum	20,000 m
- Accuracy	±5 m
Target discrimination	30 m
Extinction ratio	45 dB @ 85% reflectivity at 500 m target
Receiver optical aperture	90 mm
False alarm rate	1%, max
Laser beam-mechanical interface boresight	3 mRad
Boresighting telescope	
- Magnification	x 3.6
- Boresight with the laser beam	0.5 mRad
Cooling	Air flow (internal fan)
Communication	RS-422
Power consumption	100 W, max
Power supply	22-29 VDC, MIL-STD-704D
Weight	6.1 kg
Dimensions (L x W x H), mm	375 x 150 x 102

Elbit Systems Ltd.
Advanced Technology Center, P.O.B 539, Haifa 3100401, Israel
E-mail: istar@elbitsystems.com www.elbitsystems.com

Follow us on

The logo brand, product, service, and process names appearing herein are the trademarks or service marks of Elbit Systems Ltd., its affiliated companies or, where applicable, of other respective holders.
All information in this document is for general information only, and is subject for change without notice. © 2016. This brochure contains Elbit Systems and others proprietary information. EP2.3-MKT-041